





INSPECTORATE  
ISO 9001 : 2000

BARGE "EMS-3001"  
ENTERPRISE MARINE SERVICE  
OUTAGE TABLE

TANK NO.  
2 STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 325

Table with 14 columns (0 FT. to 14 FT.) and 34 rows. Columns represent height in feet, and rows represent measurements in barrels and gallons. The table includes data for various tank levels and gauges.

STRAPPED: 3/27/95

\* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 14'-10 3/4" (RIM OF 2" DIA. BALL VALVE  
LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE  
IN ACCORDANCE WITH APPLICABLE API STANDARDS AND  
ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

*[Signature]*  
INSPECTORATE AMERICA CORPORATION

INSPECTORATE  
ISO 9001:2000

# BARGE "EMS-3001" ENTERPRISE MARINE SERVICE OUTAGE TABLE

## TANK NO. 3 PORT OR STAR

BARGE SHOULD BE ON EVEN LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 325

M	N	0 FT.	M	N	1 FT.	M	N	2 FT.	M	N	3 FT.	M	N	4 FT.	M	N	5 FT.	M	N	6 FT.	M	N	7 FT.	M	N	8 FT.	M	N	9 FT.	M	N	10 FT.	M	N	11 FT.	M	N	12 FT.	M	N	13 FT.	M	N	14 FT.
0	0		0	0	4.518,87	0	0	4.310,31	0	0	4.081,48	0	0	3.852,88	0	0	3.623,86	0	0	3.393,19	0	0	2.959,77	0	0	2.588,34	0	0	2.216,92	0	0	1.845,49	0	0	1.474,07	0	0	1.102,55	0	0	731,22	0	0	359,80
1/4	1/4	4.528,91	1/4	1/4	4.518,87	1/4	1/4	4.310,31	1/4	1/4	4.081,48	1/4	1/4	3.852,88	1/4	1/4	3.623,86	1/4	1/4	3.393,19	1/4	1/4	2.959,77	1/4	1/4	2.588,34	1/4	1/4	2.216,92	1/4	1/4	1.845,49	1/4	1/4	1.474,07	1/4	1/4	1.102,55	1/4	1/4	731,22	1/4	1/4	359,80
1/2	1/2	4.528,91	1/2	1/2	4.518,87	1/2	1/2	4.310,31	1/2	1/2	4.081,48	1/2	1/2	3.852,88	1/2	1/2	3.623,86	1/2	1/2	3.393,19	1/2	1/2	2.959,77	1/2	1/2	2.588,34	1/2	1/2	2.216,92	1/2	1/2	1.845,49	1/2	1/2	1.474,07	1/2	1/2	1.102,55	1/2	1/2	731,22	1/2	1/2	359,80
3/4	3/4	4.528,91	3/4	3/4	4.518,87	3/4	3/4	4.310,31	3/4	3/4	4.081,48	3/4	3/4	3.852,88	3/4	3/4	3.623,86	3/4	3/4	3.393,19	3/4	3/4	2.959,77	3/4	3/4	2.588,34	3/4	3/4	2.216,92	3/4	3/4	1.845,49	3/4	3/4	1.474,07	3/4	3/4	1.102,55	3/4	3/4	731,22	3/4	3/4	359,80

\* CAPACITY BELOW STRIKE POINT

REFERENCE GAUGE HEIGHT : 14'-11" (RIM OF 2" DIA. BALL VALVE LOCATED NEAR CENTER OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

INSPECTORATE AMERICA CORPORATION